


ITEM NO:HTVE-605-9090
ITEM NO:HTVE-605-1010

User Manual




PH2
PZ2



TROUBLESHOOTING

Problem	Action
Leakage	Check the watertighteness between the base and the glass walls.
	Check the watertighteness between the base and the rails.
	Check the watertighteness between the rails and the glass walls.
Walls do not fit properly to the base	Check with a spirit level that the base is horizontal.
	Check with a spirit level that the walls are vertical.
Doors make a noise and/or do not open and close smoothly	Check with a spirit level that the shower cabinet is fastened vertically to the wall.
	Check door wheels and their lubrication.

MAINTENANCE

CLEANING

- Clean regularly with a mixture of equal parts of water and vinegar. Allow 5 minutes for it to act, and then rinse with water
- Do not use strong or abrasive detergents or solvents, this could damage the product.
  - Follow the manufacturer's instructions when using detergents. Do not use steel wool/Scotchbrite, abrasive detergents or sharp implements.
- Use bactericidal detergent on a regular basis.
- Leave the doors open after using the shower to reduce the risk of mildew.
- Rinse off residual soap etc. from the walls after use.

MAINTENANCE

- Lubricate the doors if they make a noise, or do not open and close smoothly.
- Check that all parts are correctly fitted and sealed before using the shower.
- Check that the walls are vertical and correctly fitted to each other before use.

FEILSØKING

Problem	Tiltak
Lekkasje	Kontroller vanntettheten mellom bunnen og glassvegger.
	Kontroller vanntettheten mellom bunnen og skinner.
	Kontroller vanntettheten mellom skinner og glassvegger.
Vegger ikke rettet inn mot bunnen	Kontroller med vaterpass at bunnen er horisontal.
	Kontroller med vaterpass at veggene er vertikale.
Dørene støyer og/eller beveger seg ujevnt	Kontroller med vaterpass at dusjkabinettet er vertikalt festet mot veggen.
	Kontroller hjulene på dørene og om de er smurt.


VEDLIKEHOLD

RENGJØRING


- Rengjør regelmessig med en blanding av like deler vann og eddik. La virke i 5 minutter og skyll med vann
- Ikke bruk sterke eller slipende rengjøringsmidler eller løsemidler, det kan skade produktet.
  - Følg produsentens anvisninger ved bruk av rengjøringsmiddel. Ikke bruk stålull/scotchbrite, slipende rengjøringsmidler eller skarpe gjenstander.
- Bruk regelmessig bakteriedrepende rengjøringsmiddel.
- La dørene stå åpne etter at dusjen er brukt, for å redusere faren for at det danner seg mugg.
- Skyll bort såperester og lignende fra veggene etter hver gangs bruk.

VEDLIKEHOLD

- Smør hvis dørene støyer og/eller beveger seg ujevnt.
- Kontroller at alle deler er riktig montert og tettet før du bruker vann.
- Kontroller før bruk at veggene er vertikale og korrekt tilpasset mot hverandre.


01
02
03
06
04
21A
20
07
21B
25
05
26
4X8
22
4X12
28
4X12
23
24
08
09
27
4X45
11
12
13
12
15A
19
10
14
15B
16
17
27
11

01



X 1

02



X 1

03



X 1

04




X 1

05




X 1

06



X 1

07




X 1

08




X 1

09




X 1

10




X 1

11




X 2

12




X 2

13



X 4

14



X 2

15A



short

X 2

15B



longer

X 2

16




X 2

17



X 4


18



4X12

X 4

19



X 1

20



X 1

21A



single

X 1

21B



double

X 1

22



X 2

23




X 8

24



X 1

25



X 1


26



4X8

X 5

27



4X45


X 8

28




4X12


X 18




1, Peel off the protective film




1, Install the siphon on the tray




1, Place a level ruler on the tray and adjust the support feet to ensure the tray is level.





Anbefalter å monter fronten av dusjkabinettet flatt på papp eller på mykt underlag.





Kan forskyes under transport



05
X 1
06
X 1
20
X 1
21A
single
X 1
21B
double
X 1
25
X 1



20
point rouge
06
06
21A/21B
26



22
X 2
23
X 8
24
X 1
23
24
22
23
26
22
21A
21B
24



28
4X12
X 5



12
05
28
4X12
28



28
4X12
X 5
04
X 1



04
12
28
4X12
28


26
4X8
X 5
28
4X12
X 4



26
04
05
4X8
28
4X12
Ø3.2
05
09



15B
longer
X 2
13
X 4
19
X 1
17
X 4
10
X 1



10
13
19
10
10
15B
10
17
17



14
X 2





14



01
X 1
02
X 1
28
4X12
X 4



01
26
4X12
01
4X12
26
02
02
22


03
X1


07
X1




03
07
25
07


24h